



BSP koppeling uitwendige draad vlakke afdichting type BMF



Modellen:

Bestelnummer	slangmaat	F	H	L	S	max. werkdruk bar*
C04BMF-04	1/4	1/4	25	53	19	450
C06BMF-04	1/4	3/8	27	55	22	450
C06BMF-05	5/16	3/8	27	55	22	350
C06BMF-06	3/8	3/8	27	58	22	445
C08BMF-06	3/8	1/2	32	62	27	415
C08BMF-08	1/2	1/2	33	66	27	415
C12BMF-08	1/2	3/4	36	69	32	350
C12BMF-10	5/8	3/4	36	72	32	350
C12BMF-12	3/4	3/4	37	77	32	350
C16BMF-12	3/4	1	42	82	41	280
C16BMF-16	1	1	43	94	41	280

BSP koppeling conische uitwendige draad type BMT



Modellen:

Bestelnummer	slangmaat	F	H	L	S	max. werkdruk bar*
C04BMT-04	1/4	1/4	25	53	15	350
C06BMT-04	1/4	3/8	26	54	19	280
C06BMT-05	5/16	3/8	26	54	19	280
C06BMT-06	3/8	3/8	27	57	19	280
C08BMT-06	3/8	1/2	32	63	22	280
C08BMT-08	1/2	1/2	33	66	22	280
C12BMT-10	5/8	3/4	35	71	27	280
C12BMT-12	3/4	3/4	36	77	27	280
C16BMT-16	1	1	43	94	36	280
C20BMT-20	1 1/4	1 1/4	48	106	46	210
C24BMT-20	1 1/4	1 1/2	49	110	50	185
C24BMT-24	1 1/2	1 1/2	49	114	50	185
C32BMT-32	2	2	57	127	65	175

* Attentie: let ook op de maximale werkdruk van de slang.