


MM-L

METRIC MALE 24° CONE SEAT - LIGHT DUTY
MASCHIO METRICO SVASATO 24° - SERIE LEGGERA

CEL




| TIEFFE Part.N. | Hose Size | | | METRIC 24° Connection | | Dimensions (mm) | | | | | Maximum W.P. | |
|-------------------|-----------|--------|------|--------------------------|------|-----------------|-----|----|--|--|-----------------|------|
| | DN | Inch | Dash | F | Pipe | H | L | S | | | bar | PSI |
| CX03MM6L | 5 | 3/16" | -03 | M12x1,5 | 6L | 21 | 46 | 12 | | | 280 | 4000 |
| CX03MM8L | 5 | 3/16" | -03 | M14x1,5 | 8L | 21 | 46 | 14 | | | 280 | 4000 |
| CX04MM6L | 6,3 | 1/4" | -04 | M12x1,5 | 6L | 21 | 49 | 12 | | | 280 | 4000 |
| CX04MM8L | 6,3 | 1/4" | -04 | M14x1,5 | 8L | 21 | 49 | 14 | | | 280 | 4000 |
| CX04MM10L | 6,3 | 1/4" | -04 | M16x1,5 | 10L | 23 | 51 | 17 | | | 280 | 4000 |
| CX04MM12L | 6,3 | 1/4" | -04 | M18x1,5 | 12L | 23 | 51 | 19 | | | 280 | 4000 |
| CX05MM10L | 8 | 5/16" | -05 | M16x1,5 | 10L | 23 | 51 | 17 | | | 280 | 4000 |
| CX05MM12L | 8 | 5/16" | -05 | M18x1,5 | 12L | 23 | 51 | 19 | | | 280 | 4000 |
| CX06MM10L | 10 | 3/8" | -06 | M16x1,5 | 10L | 23 | 53 | 17 | | | 280 | 4000 |
| CX06MM12L | 10 | 3/8" | -06 | M18x1,5 | 12L | 23 | 53 | 19 | | | 280 | 4000 |
| CX06MM15L | 10 | 3/8" | -06 | M22x1,5 | 15L | 25 | 56 | 22 | | | 280 | 4000 |
| CX08MM15L | 12,5 | 1/2" | -08 | M22x1,5 | 15L | 26 | 59 | 22 | | | 280 | 4000 |
| CX08MM18L | 12,5 | 1/2" | -08 | M26x1,5 | 18L | 28 | 61 | 27 | | | 210 | 3000 |
| CX10MM18L | 16 | 5/8" | -10 | M26x1,5 | 18L | 28 | 64 | 27 | | | 210 | 3000 |
| CX10MM22L | 16 | 5/8" | -10 | M30x2 | 22L | 30 | 66 | 30 | | | 210 | 3000 |
| CX12MM18L | 19 | 3/4" | -12 | M26x1,5 | 18L | 29 | 70 | 27 | | | 210 | 3000 |
| CX12MM22L | 19 | 3/4" | -12 | M30x2 | 22L | 31 | 72 | 30 | | | 210 | 3000 |
| CX16MM28L | 25 | 1" | -16 | M36x2 | 28L | 35 | 86 | 36 | | | 165 | 2400 |
| CX20MM35L | 31,5 | 1 1/4" | -20 | M45x2 | 35L | 40 | 97 | 46 | | | 100 | 1450 |
| CX24MM42L | 38 | 1 1/2" | -24 | M52x2 | 42L | 42 | 106 | 55 | | | 100 | 1450 |

MM-S

METRIC MALE - 24° CONE SEAT - HEAVY DUTY
MASCHIO METRICO - SVASATO 24° - SERIE PESANTE

CES



| TIEFFE Part.N. | Hose Size | | | METRIC 24° Connection | | Dimensions (mm) | | | | | Maximum W.P. | |
|-------------------|-----------|--------|------|--------------------------|------|-----------------|-----|----|--|--|-----------------|------|
| | DN | Inch | Dash | F | Pipe | H | L | S | | | bar | PSI |
| CX03MM6S | 5 | 3/16" | -03 | M14x1,5 | 6S | 23 | 48 | 14 | | | 415 | 6000 |
| CX03MM8S | 5 | 3/16" | -03 | M16x1,5 | 8S | 23 | 48 | 17 | | | 415 | 6000 |
| CX04MM6S | 6,3 | 1/4" | -04 | M14x1,5 | 6S | 23 | 51 | 14 | | | 450 | 6500 |
| CX04MM8S | 6,3 | 1/4" | -04 | M16x1,5 | 8S | 23 | 51 | 17 | | | 450 | 6500 |
| CX04MM10S | 6,3 | 1/4" | -04 | M18x1,5 | 10S | 24 | 52 | 19 | | | 450 | 6500 |
| CX04MM12S | 6,3 | 1/4" | -04 | M20x1,5 | 12S | 25 | 53 | 22 | | | 450 | 6500 |
| CX05MM10S | 8 | 5/16" | -05 | M18x1,5 | 10S | 24 | 52 | 19 | | | 350 | 5000 |
| CX05MM12S | 8 | 5/16" | -05 | M20x1,5 | 12S | 25 | 53 | 22 | | | 350 | 5000 |
| CX06MM10S | 10 | 3/8" | -06 | M18x1,5 | 10S | 24 | 55 | 19 | | | 445 | 6500 |
| CX06MM12S | 10 | 3/8" | -06 | M20x1,5 | 12S | 25 | 56 | 22 | | | 445 | 6500 |
| CX06MM14S | 10 | 3/8" | -06 | M22x1,5 | 14S | 27 | 58 | 22 | | | 445 | 6500 |
| CX08MM14S | 12,5 | 1/2" | -08 | M22x1,5 | 14S | 28 | 61 | 22 | | | 415 | 6000 |
| CX08MM16S | 12,5 | 1/2" | -08 | M24x1,5 | 16S | 29 | 62 | 24 | | | 415 | 6000 |
| CX10MM20S | 16 | 5/8" | -10 | M30x2 | 20S | 32 | 68 | 30 | | | 350 | 5000 |
| CX12MM20S | 19 | 3/4" | -12 | M30x2 | 20S | 33 | 74 | 30 | | | 350 | 5000 |
| CX12MM25S | 19 | 3/4" | -12 | M36x2 | 25S | 37 | 78 | 36 | | | 350 | 5000 |
| CX16MM25S | 25 | 1" | -16 | M36x2 | 25S | 39 | 90 | 36 | | | 280 | 4000 |
| CX16MM30S | 25 | 1" | -16 | M42x2 | 30S | 43 | 94 | 46 | | | 280 | 4000 |
| CX20MM30S | 31,5 | 1 1/4" | -20 | M42x2 | 30S | 44 | 101 | 46 | | | 210 | 3000 |
| CX20MM38S | 31,5 | 1 1/4" | -20 | M52x2 | 38S | 48 | 105 | 55 | | | 210 | 3000 |
| CX24MM38S | 38 | 1 1/2" | -24 | M52x2 | 38S | 48 | 112 | 55 | | | 185 | 2700 |