



Metrische wartelkoppeling "Komatsu" met 60° conus type MJF



Modellen:

Bestelnummer	slangmaat	F	H	L	S	S1	max. werkdruk bar*
C14MJF-04	1/4	M14X1,5	21,5	49,5	19	17	350
C16MJF-05	5/16	M16X1,5	22	50	22	17	350
C14MJF-06	3/8	M14X1,5	21,5	52	19	17	350
C18MJF-06	3/8	M18X1,5	22,5	53	24	19	350
C22MJF-08	1/2	M22X1,5	26	59	27	22	350
C24MJF-08	1/2	M24X1,5	30	63	32	27	350
C24MJF-10	5/8	M24X1,5	60	66	32	27	280
C30MJF-12	3/4	M30X1,5	33,5	74	36	32	280
C33MJF-16	1	M33X1,5	36	87	41	36	210
C42MJF-24	1 1/2	M42X1,5	42,5	107	50	46	105

NPT koppeling uitwendige draad type NM



Modellen:

Bestelnummer	slangmaat	F NPT	H	L	S	max. werkdruk bar*
C02NM-03	3/16	1/8	20,5	45,5	12	350
C04NM-03	3/16	1/4	26,5	51,5	14	350
C02NM-04	1/4	1/8	21	49	12	350
C04NM-04	1/4	1/4	27	55	14	350
C06NM-04	1/4	3/8	28,5	56,5	19	280
C04NM-05	5/16	1/4	27	55	14	350
C06NM-05	5/16	3/8	28,5	56,5	19	280
C04NM-06	3/8	1/4	27,5	58	16	350
C06NM-06	3/8	3/8	28,5	59	19	280
C08NM-06	3/8	1/2	34	64,5	22	280
C06NM-08	1/2	3/8	30,5	63,5	22	280
C08NM-08	1/2	1/2	35	68	22	280
C12NM-08	1/2	3/4	37	70	27	280
C08NM-10	5/8	1/2	36	72	25	280
C12NM-10	5/8	3/4	37	73	27	280
C08NM-12	3/4	1/2	37,5	78	27	280
C12NM-12	3/4	3/4	38	78,5	27	280
C16NM-12	3/4	1	45,5	86	35	280
C16NM-16	1	1	47	98	35	280
C20NM-16	1	1 1/4	51	102,1	46	210
C20NM-20	1 1/4	1 1/4	52	109,6	46	210
C24NM-24	1 1/2	1 1/2	55	119,5	50	185
C32NM-32	2	2	64	134	65	175

* Attentie: let ook op de maximale werkdruk van de slang.