


FL

SAE CODE 61 FLANGE FLANGIA SAE CODE 61

SFL




Part.N.	Hose Size			Flange Size Connection		Dimensions (mm)					Maximum W.P.	
	DN	Inch	Dash	Inch	Dash	H	L	A			bar	PSI
CS1212FL	19	3/4"	-12	3/4"	-12	55	106	38,1			350	5000
CS1216FL	19	3/4"	-12	1"	-16	57	108	44,5			350	5000
CS1220FL	19	3/4"	-12	1 1/4"	-20	55	106	50,8			280	4000
CS1612FL	25	1"	-16	3/4"	-12	58	115	38,1			350	5000
CS1616FL	25	1"	-16	1"	-16	58	115	44,5			350	5000
CS1620FL	25	1"	-16	1 1/4"	-20	63	120	50,8			280	4000
CS1624FL	25	1"	-16	1 1/2"	-24	55	116	60,3			210	3000
CS2016FL	31,5	1 1/4"	-20	1"	-16	64	131	44,5			350	5000
CS2020FL	31,5	1 1/4"	-20	1 1/4"	-20	64	131	50,8			280	4000
CS2024FL	31,5	1 1/4"	-20	1 1/2"	-24	68	135	60,3			210	3000
CS2032FL	31,5	1 1/4"	-20	2"	-32	75	142	71,4			210	3000
CS2424FL	38	1 1/2"	-24	1 1/2"	-24	73	156	60,3			210	3000
CS2432FL	38	1 1/2"	-24	2"	-32	76	159	71,4			210	3000
CS3232FL	51	2"	-32	2"	-32	77	177	71,4			210	3000
CS3240FL	51	2"	-32	2 1/2"	-40	90	187	84,1			175	2500

FL45

SAE CODE 61 FLANGE - 45° ELBOW FLANGIA SAE CODE 61 - CURVA A 45°

SFL45



Part.N.	Hose Size			Flange Size Connection		3					Maximum W.P.	
	DN	Inch	Dash	Inch	Dash	H	L	K	A		bar	PSI
CS1212FL45	19	3/4"	-12	3/4"	-12	63	114	25	38,1		350	5000
CS1216FL45	19	3/4"	-12	1"	-16	65	116	27	44,5		350	5000
CS1612FL45	25	1"	-16	3/4"	-12	81	137	31	38,1		350	5000
CS1616FL45	25	1"	-16	1"	-16	78	134	28	44,5		350	5000
CS1620FL45	25	1"	-16	1 1/4"	-20	78	134	28	50,8		280	4000
CS2016FL45	31,5	1 1/4"	-20	1"	-16	96	163	37	44,5		350	5000
CS2020FL45	31,5	1 1/4"	-20	1 1/4"	-20	91	157	32	50,8		280	4000
CS2024FL45	31,5	1 1/4"	-20	1 1/2"	-24	91	157	32	60,3		210	3000
CS2424FL45	38	1 1/2"	-24	1 1/2"	-24	108	191	36	60,3		210	3000
CS2432FL45	38	1 1/2"	-24	2"	-32	107	189	35	71,4		210	3000
CS3232FL45	51	2"	-32	2"	-32	151	245	57	71,4		210	3000
CS3240FL45	51	2"	-32	2 1/2"	-40	146	243	51	84,1		175	2500